



TECHNICAL DATA SHEET

682. TEMPEST

Water paint remover for antifouling and one-component products, for internal and external use. It does not damage gelcoat and does not dip into the epoxy undercoats. Free from harmful chemical compounds, it does not release toxic vapours.

Packaging	0,19 – 0,66 U.S. gallons (0,750 – 2,5 Lt)
-----------	-------------------------------------------

PHISICAL ASPECTS at 68 F (20° C)

Aspect	Tixotropic coloured paste
Colour	Blue
Solids (by volume)	40,74 – 81,48 sq feet/gallon (1 – 2 m ² /Lt)
Specific weight	59,85 62,37 pound/feet ³ (0,95 ÷ 0,99 g/cm ³)
Flash point	> 145,4 F (63° C)
Viscosity	25.000 cP Brookfield RTV6 at 68 F (20° C)

METHOD OF APPLICATION

Apply on the on the surface about 1 mm of product. Wait 2 to 24 hours, according to the layer to be removed. Then remove with a scraper or with high pressure water the soft mixture of TEMPEST and varnish. If necessary, repeat the process. Before painting, the surface should be carefully be washed with water and then dried up.

Application method	Brush, putty knife
--------------------	--------------------

CONDITIONS DURING THE APPLICATION

To avoid the formation of condensation, the temperature of the surface should be at least 37,4 F (3° C) above dew point. During the application and curing the min. ambient temperature must not be lower than 50 F (10° C) or higher than 86 F (30° C); substrate temperature must not be lower than 41 F (5° C), Since curing is remarkably reduced at lower temperatures. Application is not advisable when relative humidity exceeds 80%. The term-hygrometric survey should be carried out near the surface to be coated. Make sure there is enough ventilation when the application takes place in closed areas.

SAFETY RULES




In order to protect personal health it is advisable to comply with the EU DPR 303 and 547 regulations. Avoid, for example any contact of the product with the skin and eyes. In case of contamination or with oral contact, immediately contact a doctor. Use in well ventilated areas, in enclosed areas use aspirators, fans and air ventilators. Wear masks, goggles, gloves while applying the product.



TECHNICAL DATA SHEET

682. TEMPEST

NOTES

	<p>The applied product must not come in contact with water, chemical products or submitted to mechanical stress before the curing is completed. The wet film thickness is referring to an undiluted product. In case of dilution, this value increases. The above information is given to the best knowledge of Boero Bartolomeo Spa, based on laboratory tests and practical experience. However, as the product is often used under conditions beyond our control. Only the quality of the product can be guaranteed. Boero Bartolomeo Spa reserves the right to change the given data without notice. Further notes can be found in the "General recommendations" in the Supernavi paint website. For explanations, updates or further information we advise you to directly contact Boero Bartolomeo Spa The present datasheet annuls and replaces every other precedent to this one.</p>
-----------------------------------------------------------------------------------	-----------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------