



TECHNICAL DATA SHEET

703. THINNER

Universal thinner for single componets using spray gun or brush

Packaging 0,13 – 0,66 U.S. gallons (0,500 – 2.5 Lt)

PHISICAL ASPECTS at 68 F (20° C)

Aspect	Transparent
Color	Colourless
Specific weight	54,18 ÷ 56,7 pound/feet ³ (0,86 ÷ 0,90 g/cm ³)
Flash point	100,4 F (38° C)
Physical state	Liquid

CONDITIONS DURING THE APPLICATION


To avoid the formation of condensation, the temperature of the surface should be at least 5,4 F (3° C) above dew point. During the application and curing the min. surface temperature should be at 50 F (10° C), Since curing is remarkably reduced at lower temperatures. Application is not advisable when relative humidity exceeds 80%. The term-hygrometric survey should be carried out near the surface to be coated. Make sure there is enough ventilation when the application takes place in closed areas.

SAFETY RULES



In order to protect personal health it is advisable to comply with the EU DPR 303 and 547 regulations. Avoid, for example any contact of the product with the skin and eyes. In case of contamination or with oral contact, immediately contact a doctor. Use in well ventilated areas, in enclosed areas use aspirators, fans and air ventilators. Wear masks, goggles, gloves while applying the product.

NOTES



The applied product must not come in contact with water, chemical products or submitted to mechanical stress before the curing is completed. The wet film thickness is referring to an undiluted product. In case of dilution, this value increases. The above information is given to the best knowledge of Boero Bartolomeo Spa, based on laboratory tests and practical experience. However, as the product is often used under conditions beyond our control. Only the quality of the product can be guaranteed. Boero Bartolomeo Spa reserves the right to change the given data without notice. Further notes can be found in the "General recommendations" in the Supernavi paint website. For explanations, updates or further information we advise you to directly contact Boero Bartolomeo Spa The present datasheet annuls and replaces every other precedent to this one.