


1-851 Antistatic Degreaser

APPLICATION DATA




Mixing Ratio : Non applicable.




Application viscosity : Airspray (sec) : -
DINCUP 4mm/20°C : Pressure tank (sec) : -
: Airless (sec) : -
-



	<u>Nozzle diameter (mm)</u>	<u>Spraying pressure (bar)</u>
Gravity feed	-	-
Suction feed	-	-
Pressure tank	-	-
Airless	-	-
HVLP	-	See Info Manufacturer
HE	-	See Info Manufacturer



Spray coats / Layer thickness : - / -
(μm)



Flash-off (min) 20°C : -



Drying time (min) 20°C : -
60°C Obj. : -



Potlife (min) 20°C : -

1-851 Antistatic Degreaser



PRODUCT INFO

- Area of application** : Degreaser for plastics.
- Chemical base** : Special solvents and additives.
- General qualities** : Degreasing with anti-static activity. (When a surface has been cleaned with 1-851, masking-tape will not adhere. This has no effect on the adherence of the paint-system).
- Auxiliary materials** : Non applicable.

EU regulations

- VOC code** : 2004/42/IIB(a)(850)771
- Product Subcategory (according directive 2004/42/EC) and max. VOC content (ISO 11890-1/2) of the ready to use product** : IIB/a. Preparatory and cleaning - Preparatory. EU limit values: 850g/l. (2007)
 This product contains a maximum of 771 g/l VOC.

Physical properties	Specific gravity (kg/l)	: 0.783
	Flash point	: Closed cup: 28°C (82.4°F)
	Economy	: 1
	Vol.% solids	: -
	Gloss	: -
	Colour	: Clear.

- Substrates** : Plastics
- Undercoats** : n/a
- Finishing materials** : n/a
- Cleaning the equipment** : -
- Storage life (years)** : min. 5
 (Under normal storage conditions and unopened tins).

The technical data in these publications are based on our present knowledge and give you an idea of the various applications without obligations.